



TECHNICAL DATA SHEET

Date of issue: 2021

EMULSION PAINT ELITE BASIC

DESCRIPTION

Emulsion paint of excellent quality for interior use. It has great hiding power and high spreading rate. Also available in basic shades for coloring emulsion and acrylic paints.



TECHNICAL CHARACTERISTICS

Density	: 1,29 - 1,50 depending on the shade (EΛOT EN ISO 2811 20°C)
Viscosity	: 6500 - 9500cP (ASTM D2196-86 25°C)
Coverage	: 12 m ² /lt per layer
Drying time	: Touch dry after 1 hour and recoat able after 2-3hours
Colors	: Black,blue,red,yellow,ocher,tile,green,brown,orange
Packaging	: 180ml, 375ml, 750ml, 3lt, 10lt
VOC (Volatile Organic Compounds)	: EU limit value for this product Category A: "a", Type:WB, Interior matt walls and ceilings (Gloss <25@60°): 30g/l (2010). This product contains max 29g/l VOC.
Painting tools	: Brush, roller, pistol Remove as much paint as possible from the equipment in the container and clean it immediately with hot water and soap.
Conditions of application	: Do not apply at temperatures below 10°C and above 35°C.
Storage	: Store at temperatures from 5°C to 40°C. Close the container after every use.



TECHNICAL DATA SHEET

Date of issue: 2021

APPLICATION

Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances

New surfaces	1st layer: Priming with Acrylic water based primer or water based primer TETRADUR
	2nd layer: One layer of Emulsion paint Elite. Dilution 5-10% with water
	3rd layer: One layer of Emulsion paint Elite. Dilution up to 5-10% with water
Painted surfaces	Scraping, puttying and priming with Acrylic water based primer or primer TETRADUR if it's necessary and application of two layers of Emulsion paint Elite diluted 5-10% with water

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.