



## TECHNICAL DATA SHEET

Date of issue: 2021

### ACRYLIC PAINT ELITE

#### DESCRIPTION

Acrylic paint of high quality. The ratio of price to quality makes it unrivalled at the adverse weather conditions. It is suitable for concrete, plaster, etc., with great hiding power and adhesion.



#### TECHNICAL CHARACTERISTICS

|                                  |                                                                                                                                                     |
|----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| Density                          | : 1,37 - 1,51 depending on the shade (EAOT EN ISO 2811 20°C)                                                                                        |
| Viscosity                        | : 108 - 118 KU (ASTM 562)                                                                                                                           |
| Resistance to wet abrasion       | : 10.000 cycles(DIN 53778)                                                                                                                          |
| Thinning                         | : 5 - 10% with water                                                                                                                                |
| Coverage                         | : 12 m <sup>2</sup> /lt per layer                                                                                                                   |
| Drying time                      | : Touch dry after 1 hour and recoat able after 2-3hours                                                                                             |
| Colors                           | : Unlimited number of shades through tinting system of TETRALUX.                                                                                    |
| Packaging                        | : 750ml, 3lt, 10lt                                                                                                                                  |
| VOC (Volatile Organic Compounds) | : EU limit value for this product Category A: "c", Type:WB, Exterior walls of mineral substrate: 40g/l (2010). This product contains max 39g/l VOC. |
| Painting tools                   | : Brush, roller, pistol<br>Remove as much paint as possible from the equipment in the container and clean it immediately with hot water and soap.   |
| Conditions of application        | : Do not apply at temperatures below 10°C and above 35°C.                                                                                           |
| Storage                          | : Store at temperatures from 5°C to 40°C. Close the container after every use.                                                                      |



## TECHNICAL DATA SHEET

Date of issue: 2021

### APPLICATION

#### Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances

|                         |                                                                                                                                               |
|-------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| <b>New surfaces</b>     | <b>1<sup>o</sup> layer:</b> Priming with solvent based or water based primer TETRADUR                                                         |
|                         | <b>2<sup>o</sup> layer:</b> One layer of Acrylic Elite. Dilution 5-10% with water                                                             |
|                         | <b>3<sup>o</sup> layer:</b> One layer of Acrylic Elite. Dilution 5-10% with water                                                             |
| <b>Painted surfaces</b> | Scraping, puttying and priming with primer TETRADUR if it's necessary and application of two layers of Acrylic Elite diluted 5-10% with water |

### HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.